



# OPTIMIZING TOMOPY

Performance analysis of grid reconstruction

# Benchmarking: make\_data.py

```
1 import numpy as np, tomopy
2
3 obj = tomopy.shepp3d(size=512)
4 ang = tomopy.angles(750) # Generate uniformly spaced tilt angles.
5
6 sim = tomopy.project(obj, ang) # Calculate projections.
7
8 np.save('projection.npy', sim)
9 np.save('angles.npy', ang)
```

Checking dimensions and type of the projection data:

```
In [1]: import numpy as np

In [2]: sim = np.load('projection.npy')

In [3]: sim.shape
Out[3]: (750, 512, 728)

In [4]: sim.dtype
Out[4]: dtype('float32')
```

# Tomopy out of the box

```
conda create --name tomopy_nomkl \  
  -c dgursoy \  
  nomkl tomopy pyfftw fftw numpy scipy numexpr pywavelets \  
  scikit-image ipython ipython-notebook astropy \  
  python=3.5
```

```
conda create --name tomopy \  
  -c dgursoy \  
  tomopy pyfftw fftw numpy scipy numexpr pywavelets \  
  scikit-image ipython ipython-notebook astropy \  
  python=3.5
```


# Reconstruction script

```
1  import numpy as np, tomopy, time as t
2
3  def timeit(func, named_args, kwargs):
4      t0 = t.time()
5      r = func(*named_args, **kwargs)
6      t1 = t.time()
7      return (t1 - t0, r)
8
9  sim = np.load('projection.npy')
10 ang = np.load('angles.npy')
11
12 # Reconstruct object:
13 recon_time, rec = timeit(tomopy.recon, (sim, ang), dict(algorithm='gridrec'))
14
15 print("Reconstruction time: {0:.3f}".format(recon_time))
```

# Performance times

(knl)\$ numactl -p 1 \									
python recon_bench.py									
KNL	nomkl	256	47.696						
KNL	mkl	256	98.56	must set OMP_NUM_THREADS=1					
KNL	mkl	256	12.965	KMP_AFFINITY=disabled					
(hsw)\$ python									
recon_bench.py									
HSW	nomkl	32	4.246						
HSW	mkl	32	11.356						
HSW	mkl_seq	32	3.294	MKL_THREADING_LAYER=SEQUENTIAL					

# Hotspots tomopy\_nomkl on KNL




## Optimization Notice

Copyright © 2015, Intel Corporation. All rights reserved.  
\*Other names and brands may be claimed as the property of others.



# Hotspots tomopy\_nomkl on HSW



## Optimization Notice

Copyright © 2015, Intel Corporation. All rights reserved.  
\*Other names and brands may be claimed as the property of others.



# Building tomopy toolchain with icc

- Created recipes to build essential components with icc targeting common-avx512 architecture
- Small changes to tomopy itself
  - removed `-lm` in `setup.py`, vectorized code in `phantom.py`
  - changes to `gridrec.c` to enable vectorization
- Modules are `fftw`, `pyfftw`, `tomopy`, `dxchange`, `dxfile`, `olefile` are built locally
- Modules `numpy`, `scipy`, `scikit-image` are conda-installed from intel channel
- Other modules (`pywavelets`, etc) taken from `dgursoy` channel
- `netCDF4` and `atropy` were pip or conda installed



# Tomopy recipe: build.sh

```
1  #!/bin/bash
2
3  export CC=icc
4  export LDSHARED="icc -shared"
5
6  $PYTHON setup.py config
7
8  C_INCLUDE_PATH="$PREFIX/include" \
9  LD_LIBRARY_PATH="$PREFIX/lib" \
10 CFLAGS="-m64 -fomit-frame-pointer -pthread -qopenmp -fPIC -fp-model fast=2 -O3 -xCORE-AVX2 -axCOMMON-AVX512 -I$PREFIX/include $CFLAGS" \
11 LDLAGS="-L$PREFIX/lib $LDLAGS" \
12 $PYTHON setup.py build_ext --inplace
13
14 $PYTHON setup.py install --old-and-unmanageable
```

Compile tomopy using `icc` targeting both HSW and KNL, enabling vectorization.

Recipes are available on [cori](#).

Used vectorization report (`-qopt-report=5`) to guide optimizations

# Tomopy recipe, cont.

```
1  {% set version = "1.0.1" %}
2  {% set buildnumber = 6 %}
3  {% set iccver = "16.0.3" %}    [unix or py35]
4
5  package:
6    name: tomopy
7    version: {{version}}
8
9  build:
10    number: {{buildnumber}}
11    features:
12      - intel
13
14  source:
15    git_url: https://github.com/tomopy/tomopy
16    git_rev: master
17    patches:
18      - intel_changes.patch
19
20  requirements:
21    build:
22      - python
23      - intelpython
24      - icc_rt
25      - setuptools
26      - numpy
27      - fftw
```

Patch represents diff between official

[github.com/tomopy/tomopy.git](https://github.com/tomopy/tomopy.git)

and branch **feature/intelem** of its fork

[github.com/oleksandr-pavlyk/tomopy.git](https://github.com/oleksandr-pavlyk/tomopy.git)

# Gist of optimizations

- Replace `lroundf(x)` with `(int) roundf(x)`
- Replace `ceil(x)` with `ceilf(x)`, etc.
- Replace `fabs(x)` with `fabs(f)`
- Apply vectorization pragmas
- Split one double loop to enable vectorization

# Changes in gridrec.c

```
for(iu=iu1; iu<=iuh; iu++)
{
    rtmp = wtbl[lroundf(fabsf(U-iu)*tblspcg)];
    for(iv=iv1, k=0; iv<=ivh; iv++, k++)
    {
        const float convolv = rtmp*work[k];
        H[iu][iv] += convolv*Cdata1;
        H[pdim-iu][pdim-iv] += convolv*Cdata2;
    }
}
```

236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272

```
    iuh2 = (pdim2 > iuh) ? iuh : pdim2 - 1;
#pragma simd assert
    for(iu=iu1; iu <= iuh2; iu++)
    {
        rtmp = wtbl[(int) roundf(fabsf(U-iu)*tblspcg)];
        for(iv=iv1, k=0; iv<=ivh; iv++, k++)
        {
            const float convolv = rtmp*work[k];
            H[iu][iv] += convolv*Cdata1;
            H[pdim-iu][pdim-iv] += convolv*Cdata2;
        }
    }

    // assert( iu == pdim2 || iu > iuh );
    for( ; iu <= pdim2 && iu <= iuh; iu++)
    {
        rtmp = wtbl[(int) roundf(fabsf(U-iu)*tblspcg)];
        for(iv=iv1, k=0; iv<=ivh; iv++, k++)
        {
            const float convolv = rtmp*work[k];
            H[iu][iv] += convolv*Cdata1;
            H[pdim-iu][pdim-iv] += convolv*Cdata2;
        }
    }

#pragma simd assert
    for(; iu<=iuh; iu++)
    {
        rtmp = wtbl[(int) roundf(fabsf(U-iu)*tblspcg)];
        for(iv=iv1, k=0; iv<=ivh; iv++, k++)
        {
            const float convolv = rtmp*work[k];
            H[iu][iv] += convolv*Cdata1;
            H[pdim-iu][pdim-iv] += convolv*Cdata2;
        }
    }
}
```

# Building tomopy-recipe


```
1
2  #!/bin/bash
3  export CONDA_BLD_PATH=./conda-build
4
5  conda build -c intel -c dgursoy --override-channels \
6  |      --no-anaconda-upload --python 3.5 --numpy 1.11 tomopy-recipe
7  .
```

# Using built tomopy

```
1  #!/bin/bash -x
2
3  export _ENV_=$1
4
5  conda create --name $_ENV_ -c intel numpy scipy scikit-image numexpr h5py hdf5 six ipython python=3.5 --yes
6  source activate $_ENV_
7  conda install -c intel -c dgursoy --override-channels pywavelets tifffile edffile spefile --yes
8  conda install astropy --yes
9  pip install netCDF4
10
11  # install modules locally built with icc
12  pushd conda-build/linux-64
13  conda install \
14      dxchange-0.1.2-py35_intel_0.tar.bz2 \
15      fftw-3.3.6-intel_1.tar.bz2 \
16      pyfftw-0.10.4-py35_intel_0.tar.bz2 \
17      dxfile-0.4.0-py35_intel_0.tar.bz2 \
18      olefile-0.44.0-py35_intel_1.tar.bz2 \
19      tomopy-1.0.1-py35_intel_6.tar.bz2
20
```

# Performance results

python recon_bench.py									
HSW	optimized	32	1.343						
KNL	optimized	256	2.492	KMP_AFFINITY=disabled numactl -p 1 python recon_bench.py					





# Legal Disclaimer & Optimization Notice

INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS". NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO THIS INFORMATION INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

Copyright © 2015, Intel Corporation. All rights reserved. Intel, Pentium, Xeon, Xeon Phi, Core, VTune, Cilk, and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries.

## Optimization Notice

Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice.

Notice revision #20110804